# ARCHITECTURAL FX

Technicians of Light

## Neon 3D Tunable White IP67



#### **General Information**


Flexible LED strip in UV, chlorine, saltwater, solvent and heat-resistant special silicone for indoor- and outdoor use IP67 (Standard) Designed with Co-extrusion Moulding Technology 12w, 192 LED, 570 lumens per m (100% output both channels) Tunable White 2100 - 4400k (Finished CCT) Cuttable every 31.25mm (Cuttable on site at relevant marked cut points) LED spacing: 5mm Width 15mm x Height 15mm Bending diameter: 120mm Max Single length 5m, in-feeder connector and an end cap as provided Customized length with sealed connectors on request. Constant light output and extended lifetime due to an integrated constant current source on the circuit board.

#### Electrical & output data

Input Voltage 24 Volt DC Constant Voltage (23 V min, 25 V max) Working Temperature range: -20 to +55°C Storage temperature Ts min = 0°C, Ts max = 60°C Dimmable – 0-10v, Dali, DMX Protected against electrostatic discharge +/- 2,000 V

Lifetime and Warranty (See full Architectural FX total system warranty for more detail)

Lifespan L70: 36,000 hours Product availability lifetime – 3 years from last order End of Lifetime guarantee 5 years The above data are typical values. Due to tolerances in the production process and electrical components, Values for light output and electrical power can vary up to 10%.





Maximum bending radius 60mm (See Installation manual for more detail)

**Product Reference builder** 

Generic Product	Product Type	Bend Orientation	Colour (Finished CCT)	w/m	Mounting Accessory	Cable Entry
Neon	3D	All (Side, Top, Twist)	2100 - 4400k	12w	MP - Mounting Profile	End (Standard)

Product reference: Neon 3D 2100-4400k 12w IP67 (Custom length to suit project to be advised)




### Mounting and connecting accessories


Aluminium mounting profile 2000mm or mounting clip 50mm









Flexible mounting profile Top or Side Bend or 3D 500mm



(Indicates product inside profile)

#### Plaster In mounting profile Top or Side Bend or 3D 1000mm





Unit 16 The Business Centre Molly Millars Lane Wokingham RG41 2QY T +44 (0)1344 291536 E sales@afx.lighting www.afx.lighting