


Platin Ultra TVQ (Top Bend) IP67



General Information

Flexible LED strip in UV, chlorine, saltwater, solvent and heat-resistant special silicone for indoor- and outdoor use, IP67
15w, 108 LED, 840 lumens per m
2200, 2500, 2700, 3000, 4000k (Finished CCT)
Cuttable every 55.6mm or 6 LEDs
LED spacing: 9.3mm
Width 16mm x Height 17mm
Easy installation due to solder-free connectors.
Bending diameter: 300mm
Max Single length 8m, in-feeder connector and an end cap as provided
Customized length with sealed connectors on request.
Constant light output and extended lifetime due to an integrated constant current source on the circuit board.

Electrical & output data

Input Voltage 24 Volt DC Constant Voltage (23 V min, 25 V max)
Ambient operating Temperature range: -40 to +70 °C
Storage temperature Ts min = -30°C, Ts max = 85°C
Dimmable – Mains (Triac), 0-10v, Dali, DMX
Protected against electrostatic discharge +/- 2,000 V

Lifetime and Warranty (See full Architectural FX total system warranty for more detail)

Lifespan L70: 50,000 hours
Product availability lifetime – 3 years from last order
End of Lifetime guarantee 5 years
The above data are typical values. Due to tolerances in the production process and electrical components, values for light output and electrical power can vary up to 10%.


Product Reference builder

Generic Product	Product Type	Bend Orientation	Colour (Finished CCT)	w/m	Mounting Accessory	Cable Entry
Platin	White	Top	2200k	15w	MC - 50mm Clip	End (Standard)
			2500k		MP – Mounting Profile	Side Left - SL
			2700k			Side Right – SR
			3000k			Rear - R
			4000k			

Example:

Platin Ultra TVQ 2700k 15w MC E (Custom length to suit project to be advised)

Customized length with sealed connectors on request.



***IP20 quick connects available, along with quick seal end entry connections from stock**

Compatible Accessories (See Accessories data sheet for full details)



Note: Do not twist or bend against bend orientation on install

