

Titanium SVQ (Top View Side Bend) IP67



General Information

Flexible LED strip sealed in UV, chlorine, salt-water and solvent-resistant white PVC, for indoor and outdoor use
IP67 rated

4w, 9w, 14w, 17w per m Up to 1641 lumens per m (from 50lm/w up to 117lm/w)

Single Colour White 2400k, 2600k, 2900k, 3700k (Finished CCT)

RGB

CRI >90

Cuttable every 62.25mm

Width 15mm x Height 19mm

Bending diameter 300mm

Max Single length 5m (Dependent on w/m)

Electrical & output data

Input Voltage 24 Volt DC Constant Voltage (23 V min, 25 V max)

Ambient temperature: -25 to +50°C

Storage temperature Ts min = -30°C, Ts max = 85°C

Dimmable – Mains (Triac), 0-10v, Dali, DMX

Protected against electrostatic discharge +/- 2,000 V

Lifetime and Warranty (See full Architectural FX total system warranty for more detail)

Lifespan L70: 60,000 hours

Product availability lifetime – 3 years from last order

End of Lifetime guarantee 5 years

The above data are typical values. Due to tolerances in the production process and electrical components, values for light output and electrical power can vary up to 10%.



Energy efficiency class



Product Reference builder

Generic Product	Product Type	Bend Orientation	Colour (Finished CCT)	w/m	Lumens/m	Max Single length
Titanium	Titanium SVQ	Side	2400k	4w	261	4.5m
Titanium	Titanium SVQ	Side	2600k	4w	282	4.5m
Titanium	Titanium SVQ	Side	2900k	4w	307	4.5m
Titanium	Titanium SVQ	Side	3700k	4w	370	4.5m
Titanium	Titanium SVQ	Side	2400k	9w	555	4.5m
Titanium	Titanium SVQ	Side	2600k	9w	601	4.5m
Titanium	Titanium SVQ	Side	2900k	9w	677	4.5m
Titanium	Titanium SVQ	Side	3700k	9w	792	4.5m
Titanium	Titanium SVQ	Side	2400k	14w	701	4.5m
Titanium	Titanium SVQ	Side	2600k	14w	1239	4.5m
Titanium	Titanium SVQ	Side	2900k	14w	1323	4.5m
Titanium	Titanium SVQ	Side	3700k	14w	1641	4.5m
Titanium	Titanium SVQ	Side	RGB	17w	368	4m

Example:

Titanium SVQ 2400k 9w IP67 (Custom length to suit project to be advised). Customized length with sealed connectors on request.



***Bottom feed, End connection only for Butt join, continuous illumination**

Compatible Accessories (See Accessories data sheet for full details)



Note: Do not twist or bend against bend orientation on install

