


Integrate RGBWH

General Information

- Flexible LED strip IP20
- 24v DC Constant Voltage
- Beam angle: 120°
- CRI >98
- R9 >95
- Increments 83.3mm
- LED pitch: 13.8mm
- Lifespan L90: ≥ 60,000 hours
- Dimmable – DALI, DMX
- Max Ambient operating temperature (15w/m 50°C, 25w/m 45°C)
- Available IP40, IP44, IP67
- 7 Year warranty (Limited to 5,000hrs per year running)



Integrate LED Code	CCT	20w/m	40w/m
		lm/m	lm/m
RGBWH	3000k	560/940	790/2920
RGBWH	4000k	560/980	790/3020

Note: -40% light loss with Opal cover

About the Light source:

24v, flexible LED strip with reflective, white surface and 3M adhesive tape on the back. Homogeneous light source for fixtures with Opal covers <15mm from LED to Opal cover. Osram LEDs of the highest quality. 120° beam angle.

“One Bin Only” within 3 MacAdam

Integrated Constant Current technology to guarantee Constant color and Intensity over from first to last LED over lifetime

About the Fixtures:

A portfolio of Aluminium Recessed, Surface Mounted, Suspended or Plaster-In profiles, covers and mounting accessories for Interior, Exterior architectural and commercial applications.

(See separate pdf catalogue and specification builder for options)