


LTwo® MAG – 100° diffuse

constant current

25 watt/m



reddot winner 2023




Length	142 mm	282 mm	562 mm	842 mm	1.122 mm	1.402 mm
Power	3,6 W	6,9 W	13,5 W	20,1 W	26,6 W	33,3 W
Lumen	631 lm	1.262 lm	2.525 lm	3.787 lm	5.050 lm	6.312 lm

Product description

LTwo® – Light Tube with Optics. Diffuse cover with max. 6,436 lumen, based on the modular, miniaturised LTwo® light source/ luminaire system with 13 high-quality precision optics and extensive accessories for all lighting applications. With newly developed, multifunctional lamp/luminaire holder for easy, tool-free, magnetic installation and angle adjustment in +/-20°, as well as locking. Coded socket for safe operation of lamp luminaires with different operation modes in Constant Voltage or Constant Current. Very environmentally friendly due to minimal use of material (180g/m), interchan-geability, recyclability and high efficiency (up to 193 lm/W). Ideally suited for building and material integration as well as the construction of luminaires or use with a wide range of accessories from apl.

Light distribution



LTwo® schwarz / black – 100° diffuse, 562mm

Application

Ideal when uniform light distribution without hard shadows and with high efficiency is required.

Order code

Product	OP	NP	Optic	L	PC	C	LH	IP
APL-LTwoT5	CV	12	10				MAG	IP40
				282	927	BB		
				562	930	WW		
				842	935			
				1122	940			
				1402	850			

OP = Operating mode
 CV = Constant Voltage
 CC = Constant Current
NP = Nominal power per m (W/m)
 12-25 = 12 W/m | 20 W/m | 25 W/m
Optic = Optic (Degree)
 10-60 = 10° HB | 13° | 25° | 40° | 60°
 BWN | BWV = Batwing narrow | Batwing wide
 OVL | WW = Oval | Wall washer
 OP | DF | CL = Opal | Diffuse | Clear


L = Length (mm)
 142-1402 = 142 mm | 82 mm | 62 mm | 42 mm | 122 mm | 402 mm
PC = Photometric code
 927-950 = CRI >90 | CRI >80 | 2.700K | 3.000K | 3.500K | 4.000K | 5.000K
C = Housing colour
 BB | WW = Black | White
LH = Luminaire holder
 MAG = Magnetic luminaire holder
IP = Protection class
 IP40 = Indoor use only



Under the following link you will find the tender specification for the product:

<https://apl.ag/products/>

LTwo® accessories



LTwo® magnetic lampholder

The "LTwo® magnetic lamp holder" is required to operate the LTwo®. Select the "PIT block" variant to connect the lamp holder to the ballast with its own cable. If you prefer a plug-in solution, then select the "JST" variant. To connect this variant to the ballast, the "3-pole cable set with JST" is required. Alternatively, you can choose a pre-wired ballast, in which the cable set is already permanently connected to the ballast. There are a wide range of accessories for mounting the lamp holder. Please refer to our accessories catalog. The accessories are optimized to realize your own lighting project and to easily integrate the LTwo® into all types of materials or the building.



LTwo® to use in track lighting systems

In existing track lighting systems, use the Lumami® TRACK. No further accessories are required here.




LTwo® as linear Downlight To use the LTwo as a linear downlight from the standard mounting holes, use Lumami® DOWNLIGHT.



LTwo® to use in apl luminaires

If you choose an apl luminaire (e.g. Lumami® DESK), no further accessories are required.



LTwo® into your project Please contact us at the following service address. We will be happy by integrating LTwo® in your project.
info@apl.ag